




Make Presentation simple
Make installation easier

WENGO Z-LEASE series - indoor rental display, is designed for indoor places of large-screen rental display equipment, the biggest advantage lies in its flexibility, thin and lightweight quick box design, a single person can be independently and quickly on-site installation, with a small size, low power consumption, long service life, low heat, environmental protection and energy saving, etc., is widely used in concerts, sporting events, exhibitions, business promotions, conferences and celebrations, and other temporary or long-term activities. It is widely used in concerts, sports events, exhibitions, commercial displays, conferences, celebrations and other temporary or long-term activities.





High Quality Driver Power Supplies



High-quality production process




Highly demanding production processes




Product front



Product Side



500*500mm Back of the product




500*1000mm Back of the product













Standard Case Size

1000mm*500mm and 500mm*500mm choose universal 250*250mm module.



Box Illustration




Support for front and back maintenance

Modular design, module, power supply box and case can be disassembled separately Enables quick maintenance in different situations




Back maintenance




Positive maintenance

Corner protection

Anti-touch protection corner effectively solves the problem of lamp bead mask damage during transportation.








Module mask for all-around protection


Effectively prevent the impact of collision on the LED lamp beads, not easy to fall off



Mask protection








Upper and lower double lock design


Single box with double lifting lock design
Steel core double spring latch for efficient and fast installation






High quality plug power cord and 6AT network cable

Convenient unplugging/plugging, self-developed quality and durability



High precision CNC die-cast aluminum case


One-piece CNC die-cast aluminum case for higher precision and stability






Inner and outer arc splicing

Innovative self-locking mechanism for smoother arc adjustment





Optional outdoor waterproof case


IP65 rated for direct rainfall
Can cope with a variety of outdoor environments, and can still operate stably in harsh environments.




Variety of options for customization

Right Angle, Arc, Circle
Diversified customization to meet the different needs of a variety of occasions











More Application Areas

Bars and nightclubs




Mall Promotions




vocal recital or concert





System Expansion Diagram



-network cable------fiber optic cable -

Audio Signal/Serial Cable

video cable

Product Parameters

model number	P1.5625	P1.95	P2.604	P2.976	P3.91	P4.81
Pixel pitch	1.5625	1.95	2.604	2.976	3.91	4.81
Light bulb	SMD1212(GOB)	SMD1515	SMD1515	SMD1515	SMD2020	SMD2020
Horizontal and vertical viewing angles	160°	160°	160	160°	160°	160°
pixel composition	1R1G1B	1R1G1B	1R1G1B	1R1G1B	1R1G1B	1R1G1B
Pixel density	409600 points/m ²	262144 points/m ²	147456 points/m ²	112896 points/m ²	65536 points/m	43264 points/m ²
Scanning method	14611	11689	11689	45319	45307	45304
Grayscale level	16BIT	16BIT	16BIT	16BIT	16BIT	16BIT
Luminance	600	800	800	800	1000	1000
Contrast	1/10000	1/10000	1/10000	1/10000	1/10000	1/10000
Frame rate	60FPS	60FPS	60FPS	60FPS	60FPS	60FPS
Refresh rate	3840Hz	3840Hz	3840Hz	3840Hz	3840Hz	3840Hz
Input Voltage	DC5V	DC5V	DC5V	DC5V	DC5V	DC5V
Peak power consumption	600W	600W	600W	600W	600W	600W
Weights	13KG/m²	13KG/m²	13KG/m²	13KG/m²	13KG/m²	13KG/m²
Service life	>100.000H	>100,000H	>100,000H	>100,000H	>100,000H	>100,000H
Waterproof rating	IP31	IP31	IP31	IP31	IP31	IP31
fire rating	VO	V0	V0	V0	V0	V0
Module Pixel	160*160	128*128	96*96	84*84	64*64	52*52
Module Size	250*250mm	250*250mm	250*250mm	250*250mm	250*250mm	250*250mm
Box size	500*500/500*1000	500*500/500*1000	500*500/500*1000	500*500/500*1000	500*500/500*1000	500*500/500*1000

